

# Model 4014-CM



## STANDARD FEATURES

- Punching Capacity 40 Tons
- Keyed Punch Ram for Safety
- 6" Throat Depth
- Angle Shear Capacity  
3" x 3" x 5/16" and 2" x 2" x 1/4" at 45 Degrees
- Bar Shear Capacity 14". Blades Complete with 4 Cutting Edges
- Tool Table Work Area for Mounting Optional Tooling
- 2" Die Holder, Jam Nut and Stripper
- Jam Nut Wrench
- Adjustable Stroke Controls
- Electrical Box Supplied with Emergency Palm Button and Lock-out Tag-out Accommodations
- 230/460 Volt 3 Phase Electrics (must specify voltage)
- All Guards Necessary to Comply with ANSI B 11-5 Standards
- Fork Lift Accommodations
- One Year Warranty

## CAPACITIES & SPECIFICATIONS RATED ON 65,000 PSI TENSILE, A 36 MILD STEEL

Throat Depth	6"	150 mm	Angle Shear 90	3" x 3" x 5/16"	75 x 75 x 8	Pipe Notching Schedule 40 I.D.	3/4", 1", 1-1/4", 1-1/2", 2"	20, 25, 32, 38, 50
Punching Capacity	40 ton	36 mt	Angle Shear 45	2" x 2" x 1/4"	50 x 50 x 6	Brake 8"	25 ton	23 mt
	1" IN 1/2"	25 IN 12	Strokes Per Minute			12"	20 ton	18 mt
Special Tooling	2-1/4" Max. Dia.	57 Max. Dia.	Lt. Material - 1/4" stroke	40		Hydraulics	1350 psi	93 bar
Flat Bar Shear	14" Length	355	Heavy Mat. - 3/4" stroke	17		Standard	230/460 3 hp 3 ph	2.24 kW
	1/2" x 6"	12 x 150	Pickett Tool	1/2", 3/4" & 1"	12, 19, 25		200/208/340/380	
	3/8" x 10"	10 x 203	Rod/Angle Shear Combo	2" x 2" x 1/4"	50.8 X 50.8 X 6.35	Optional	400/415/550/575	
	1/4" x 12"	6 x 250	Round	3/4" Max.	20 Max.		220 5 hp 1 ph	
	3/16" X 14"	5 x 355	Square	3/4" Max.	20 Max.	Dimensions	W-26" L-50" H-53"	W-66 L-127 H-135 cm
Opt. Saber Blade	1/2" x 8"	12 x 200	90 V. Notcher	6" x 6" x 1/8"	150 x 150 x 3	Weight	1,117 lbs.	532 kg
	1/4" x 14"	6 x 355	Rectangle Notcher	2" x 1-3/4" x 1/4"	50 x 45 x 6			